APT-BDFDF-DB 苏州启道 - 康普安德鲁HELIAX中国区独家授权总代理



Product Classification

Arrestor Plus® Dual Band Quarterwave Surge Arrestor (T-shaped), 806–960 MHz and 1700–2170 MHz, with interface types DIN Female Bulkhead and DIN Female

| Product Type | Surge arrestor |
|----------------------------|---------------------------------|
| Product Brand | Arrestor Plus® |
| Ordering Note | CommScope® non-standard product |
| General Specifications | |
| Device Type | dc Block |
| Body Style | Bulkhead |
| Inner Contact Plating | Silver |
| Interface | 7-16 DIN Female Bulkhead |
| Interface 2 | 7-16 DIN Female |
| Outer Contact Plating | Trimetal |
| Pressurizable | No |
| Dimensions | |
| Height | 74.93 mm 2.95 in |
| Width | 41.91 mm 1.65 in |
| Length | 80.01 mm 3.15 in |
| Electrical Specifications | |
| 3rd Order IMD | -117 dBm |
| 3rd Order IMD Test Method | Two +43 dBm carriers |
| Insertion Loss, typical | 0.07 dB |
| Average Power at Frequency | 3,000.0 W @ 900 MHz |
| Connector Impedance | 50 ohm |
| | |

Page 1 of 3

©2021 CommScope, Inc. All rights reserved. All trademarks identified by ® or [™] are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: November 18, 2020



APT-BDFDF-DB 苏州启道 - 康普安德鲁HELIAX中国区独家授权总代理

| Lightning Surge Capability | 100 times @ 20 kA |
|--|---|
| Lightning Surge Capability Test Method | IEEE C62.42-1991 |
| Lightning Surge Capability Waveform | 8/20 waveform |
| Lightning Surge Current | 30 kA |
| Lightning Surge Current Waveform | 8/20 waveform |
| Operating Frequency Band | 1710 – 2000 MHz 2000 – 2170 MHz 806 – 960 MHz |
| Peak Power, maximum | 40 kW |
| Throughput Energy at Current | 2.0 mJ @ 30 kA 25.0 μJ @ 2 kA |
| Throughput Energy Waveform | 8/20 waveform |

VSWR/Return Loss

| Frequency Band | VSWR | Return Loss (dB) |
|----------------|------|------------------|
| 806–960 MHz | 1.11 | 26 |
| 1710-2000 MHz | 1.12 | 25 |
| 2000–2170 MHz | 1.11 | 26 |

Mechanical Specifications

| Attachment Durability | 25 cycles |
|------------------------------|---|
| Interface Durability | 500 cycles |
| Interface Durability Method | IEC 61169-16:9.5 |
| Mechanical Shock Test Method | MIL-STD-202F, Method 213B, Test Condition C |

Environmental Specifications

| Operating Temperature | -40 °C to +150 °C (-40 °F to +302 °F) |
|------------------------------------|---|
| Storage Temperature | -40 °C to +100 °C (-40 °F to +212 °F) |
| Attenuation, Ambient Temperature | 20 °C 68 °F |
| Average Power, Ambient Temperature | 40 °C 104 °F |
| Corrosion Test Method | MIL-STD-202, Method 101, Test Condition B |
| Immersion Depth | 1 m |
| Immersion Test Mating | Mated |
| Immersion Test Method | IEC 60529:2001, IP68 |
| Moisture Resistance Test Method | MIL-STD-202, Method 106 |
| Thermal Shock Test Method | MIL-STD-202, Method 107, Test Condition A-1, Low Temperature -55 °C |

Page 2 of 3

©2021 CommScope, Inc. All rights reserved. All trademarks identified by ® or [™] are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: November 18, 2020



APT-BDFDF-DB 苏州启道 - 康普安德鲁HELIAX中国区独家授权总代理

Vibration Test Method

GR 2846-CORE

Water Jetting Test Mating

Mated

Packaging and Weights

Weight, net

0.63 kg | 1.39 lb

Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|--|
| CHINA-ROHS | Above maximum concentration value |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| REACH-SVHC | Compliant as per SVHC revision on www.commscope.com/ProductCompliance |
| ROHS | Compliant/Exempted |
| | |

* Footnotes

Insertion Loss, typical0.05v⁻freq (GHz) (not applicable for elliptical waveguide)Immersion DepthImmersion at specified depth for 24 hours

Page 3 of 3

©2021 CommScope, Inc. All rights reserved. All trademarks identified by ® or [™] are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: November 18, 2020

