

Coaxial Cable
ENVIROFLEX_179

苏州启道 — 中国区优势专业供应商
sales@qiidao.com

Description

PE Foam cross-linked - 75 Ohm - single screen (UL AWM Style 3651)



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Steel, Copper+Silver plated	Strand-07	0.305 mm
Dielectric	SPEX (Crosslink Foam PE)		1.55 mm
Outer conductor	Copper, Silver plated	Braid, 94%	2 mm
Jacket	RADOX	RAL 5015 - bl	2.54 mm +/- 0.07

Print: HUBER+SUHNER ENVIROFLEX 179 75 Ohm (UL logo) AWM Style 3651 (PA no.)

Electrical Data

Impedance	75 Ω +/- 3
Operating Frequency	3 GHz
Capacitance	63 pF/m
Velocity of signal propagation	70 %
Signal delay	4.78 ns/m
Insulation resistance	≥ 1 x 10 ⁷ MQm
Min. screening effectiveness	≥ 40 dB (up to 1 GHz)
Max. operating voltage	≤ 1 kV _{rms} (at sea level)
Test voltage	2 kV _{rms} (50 Hz/1 min)
Voltage Rating UL	300 V
Phase vs Temperature	-40°C... + 100°C
Phase vs Bending	8400 ppm
	0.7 °/GHz

Mechanical Data

Weight	1.11 kg/100 m
Min. bending radius	static repeated (for ≤ 50 bendings) 5 mm 25 mm

Environmental Data

Temperature range	-40 °C... +105 °C
Temperature Rating UL	105 °C
Installation temperature	-20 °C... +60 °C
Flammability	UL 1581 § 1100, IEC 60332-2, EN 60332-1-2
Smoke density	EN 61034-2
Halogen test	IEC 60754
Uv resistance test	IEC 60068-2-5, proc. C
Solar radiation	IEC 60068-2-5, proc. C
2011/65/EU (RoHS)	compliant

Additional Information

Railway certificates discontinued by end of 2017. Replacement type for railway: RADOX_RF_179.

Ordering Information

Order as	ENVIROFLEX_179
----------	----------------

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group	U5 2 mm / 75 Ohm
-------------	------------------

Coaxial Cable
ENVIROFLEX_179

苏州启道 — 中国区优势专业供应商

sales@qiidao.com
Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p / f^{0.5})$]

Coefficients:

 $a = 0.8288$
 $b = 0.0725$
 $f_{\max} = 3$
 $P \text{ at } 1\text{GHz} = 45$

Frequency (GHz)	Nom. attenuation (dB / m)	Nom. attenuation (dB / ft)	Max. CW power (watt)
	sea level 25° C ambient temperature	sea level 25° C ambient temperature	sea level 40° C ambient temperature
0,15	0,33	0,101	116
0,3	0,48	0,145	82
0,45	0,59	0,179	67
0,6	0,69	0,209	58
0,75	0,77	0,235	52
0,9	0,85	0,260	47
1,05	0,93	0,282	44
1,2	0,99	0,303	41
1,35	1,06	0,323	39
1,5	1,12	0,343	37
1,65	1,18	0,361	35
1,8	1,24	0,379	34
1,95	1,3	0,396	32
2,1	1,35	0,412	31
2,25	1,41	0,429	30
2,4	1,46	0,444	29
2,55	1,51	0,460	28
2,7	1,56	0,475	27
2,85	1,61	0,489	27
3,0	1,65	0,504	26