

Coaxial Cable
Enviroflex_B316_D

苏州启道 — 中国区优势专业供应商
sales@qiidao.com

Description

PE Foam - 50 Ohm - double screen



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Steel, Copper+Silver plated	Strand-07	0.54 mm
Dielectric	SPE (Foamed Polyethylene)		1.5 mm
Outer conductor	Copper, Tin plated	Braid, 95%	2 mm
Outer conductor	Copper, Tin plated	Braid, 85 %	2.4 mm
Jacket	LSFH (modified polyethylene)	RAL 9005 - bk	3.16 mm +/- 0.1

Print: HUBER+SUHNER ENVIROFLEX B316 D 50 OHM (PA no.)

Electrical Data

Impedance	50 Ω +/- 2
Operating Frequency	6 GHz
Capacitance	94.5 pF/m
Velocity of signal propagation	71 %
Signal delay	4.7 ns/m
Insulation resistance	≥ 1 x 10 ⁷ MΩm
Min. screening effectiveness	≥ 60 dB (up to 6 GHz)
Max. operating voltage	≤ 1.3 kV _{rms} (at sea level)
Test voltage	3 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight	1.9 kg/100 m
Min. bending radius	static repeated (for ≤ 50 bendings) dynamic
	5 mm
	30 mm
	30 mm

Environmental Data

Temperature range	-40 °C... +85 °C
Installation temperature	-20 °C... +60 °C
Flammability	IEC 60332-1,
Thermal stress test	IEC 61196-1 § 10.9
2011/65/EU (RoHS)	compliant

Additional Information

Ordering Information

Order as	Enviroflex_B316_D
----------	-------------------

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group	U4 2 mm / 50 Ohm
-------------	------------------

Coaxial Cable
Enviroflex_B316_D

 苏州启道 — 中国区优势专业供应商
sales@qiidao.com
Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p / f^{0.5})$]

Coefficients:

a = 0.7648

b = 0.1301

f_{max} = 6

P at 1GHz = 70

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (watt) sea level 40° C ambient temperature
0,3	0,46	0,140	128
0,6	0,67	0,204	90
0,9	0,84	0,257	74
1,2	0,99	0,303	64
1,5	1,13	0,345	57
1,8	1,26	0,384	52
2,1	1,38	0,421	48
2,4	1,5	0,456	45
2,7	1,61	0,490	43
3,0	1,71	0,523	40
3,3	1,82	0,554	39
3,6	1,92	0,585	37
3,9	2,02	0,615	35
4,2	2,11	0,644	34
4,5	2,21	0,673	33
4,8	2,3	0,701	32
5,1	2,39	0,729	31
5,4	2,48	0,756	30
5,7	2,57	0,783	29
6,0	2,65	0,809	29