

## FPS Series

## 0.5–18GHz Divide-By-2 Prescaler

### Features

- Input Frequency: 0.5-18GHz
- Output Frequency: 0.25-9GHz
- Divide Ratio: 2
- Output Power: -4dBm
- Phase Noise: -147dBc/Hz
- DC Power: 12V
- Internal Voltage Regulator
- Reverse Voltage Protection
- SMA Female Connector

### Picture



### Description

FPS-2-18 is a wideband frequency 0.5 – 18GHz divider with divide ratio of 2.


### Electrical Specifications @ +25 °C, $Z_{IN} = Z_{OUT} = 50 \Omega$ , DC Supply = +12V

| Parameter                       | Unit   | Minimum | Typical | Maximum |
|---------------------------------|--------|---------|---------|---------|
| Input Frequency Range           | GHz    | 0.5     |         | 18      |
| Output Frequency Range          | GHz    | 0.25    |         | 9       |
| Fixed Divide Ratio              |        |         | 2       |         |
| Input Power Range               |        |         |         |         |
| f = 0.5GHz – 1GHz               | dBm    | +3      | +5      | +10     |
| f = 1GHz – 2GHz                 | dBm    | -10     | 0       | +10     |
| f = 2GHz – 14GHz                | dBm    | -15     | 0       | +10     |
| f = 14GHz – 16GHz               | dBm    | -15     | 0       | +5      |
| f = 16GHz – 18GHz               | dBm    | -10     | 0       | +3      |
| Output Power                    |        |         |         |         |
| f = 0.5GHz – 18GHz              | dBm    | -7      | -4      |         |
| SSB Phase Noise (100KHz Offset) | dBc/Hz |         | -147    |         |
| DC Power Supply                 | V      | 9       | 12      | 15      |
| Supply Current                  | mA     |         | 85      | 100     |

## FPS Series

## 0.5–18GHz Divide-By-2 Prescaler

Typical Performance @ +25 °C



Tested with  $P_{in}=0\text{dBm}$

## FPS Series

## 0.5–18GHz Divide-By-2 Prescaler

### Absolute Maximum Ratings


| Parameter             | Absolute Maximum  |
|-----------------------|-------------------|
| RF Input Power        | +13dBm            |
| Supply Voltage        | +16V              |
| Operating Temperature | -40 °C to +85 °C  |
| Storage Temperature   | -55 °C to +125 °C |

### ESD Sensitive Material



**WARNING: MUST USE HEAT SINK IF CASE TEMPERATURE EXCEEDS 50 °C**

### Outline



|      | A     | B     | C     | D     | E     | F     | G     | H     | I     | J     |
|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Inch | 1.250 | 1.250 | 0.563 | 0.450 | 1.000 | 0.625 | 1.000 | 0.250 | 0.500 | 0.187 |
| mm   | 31.75 | 31.75 | 14.29 | 11.43 | 25.40 | 15.88 | 25.40 | 6.35  | 12.70 | 4.76  |