

Coaxial Cable
K_01152-16

苏州启道 — 中国区优势专业供应商
sales@qiidao.com

Description

PFA - 50 Ohm - single screen



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Steel, Copper+Silver plated	Wire	0.18 mm
Dielectric	PFA (Perfluoroalkoxy)		0.48 mm
Outer conductor	Copper, Silver plated	Braid, 96.8%	0.84 mm
Jacket	PFA (Perfluoroalkoxy)	Nature	1 mm +/- 0.05

Print: (no print)

Electrical Data

Impedance	50 Ω +/- 5
Operating Frequency	3 GHz
Capacitance	96.6 pF/m
Velocity of signal propagation	69 %
Signal delay	4.83 ns/m
Insulation resistance	≥ 1 x 10 ⁸ MΩm
Min. screening effectiveness	≥ 40 dB (up to 3 GHz)
Max. operating voltage	≤ 0.25 kV _{rms} (at sea level)
Test voltage	1 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight	0.33 kg/100 m
Min. bending radius	static repeated (for ≤ 50 bendings) 12 mm 20 mm

Environmental Data

Temperature range	-55 °C... +165 °C
Installation temperature	-20 °C... +60 °C
2011/65/EU (RoHS)	compliant

Additional Information

Ordering Information

Order as	K_01152-16
----------	------------

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group	U99 Customer Specific
-------------	-----------------------

Coaxial Cable
K_01152-16

苏州启道 — 中国区优势专业供应商

sales@qiidao.com
Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p / f^{0.5})$]

Coefficients:

 $a = 1.984$
 $b = 0.066$
 $f_{\max} = 3$
 $P \text{ at } 1\text{GHz} = 15$

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (watt) sea level 40° C ambient temperature
0,15	0,78	0,237	39
0,3	1,11	0,337	27
0,45	1,36	0,415	22
0,6	1,58	0,480	19
0,75	1,77	0,539	17
0,9	1,94	0,592	16
1,05	2,1	0,641	15
1,2	2,25	0,687	14
1,35	2,39	0,730	13
1,5	2,53	0,771	12
1,65	2,66	0,810	12
1,8	2,78	0,847	11
1,95	2,9	0,884	11
2,1	3,01	0,919	10
2,25	3,12	0,952	10
2,4	3,23	0,985	10
2,55	3,34	1,017	9
2,7	3,44	1,048	9
2,85	3,54	1,078	9
3,0	3,63	1,108	9