

Coaxial Cable
K_01252_D

苏州启道 — 中国区优势专业供应商
sales@qiidao.com

Description

PTFE - 50 Ohm - double screen



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Steel, Copper+Silver plated	Strand-07	0.31 mm
Dielectric	PTFE (Polytetrafluoroethylene)		0.83 mm
Outer conductor	Copper, Silver plated	Braid, 95%	1.33 mm
Outer conductor	Copper, Silver plated	Braid, 92 %	1.83 mm
Jacket	FEP (Fluorinated ethylene propylene)	RAL 8015 - br	2.4 mm +/- 0.1

Print: HUBER+SUHNER K 01252 D 50 Ohm (PA no.)

Electrical Data

Impedance	50 Ω +/- 2
Operating Frequency	6 GHz
Capacitance	97 pF/m
Velocity of signal propagation	69 %
Signal delay	4.84 ns/m
Insulation resistance	≥ 1 x 10 ⁸ MQm
Min. screening effectiveness	≥ 80 dB (up to 6 GHz)
Max. operating voltage	≤ 0.5 kV _{rms} (at sea level)
Test voltage	1 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight	1.5 kg/100 m
Min. bending radius	static repeated (for ≤ 50 bendings) dynamic
	15 mm
	24 mm
	36 mm

Environmental Data

Temperature range	-65 °C... +165 °C
Installation temperature	-20 °C... +60 °C
Flammability	IEC 60332-3, compliant
2011/65/EU (RoHS)	

Additional Information

Ordering Information

Order as	K_01252_D
----------	-----------

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group	X1 1 mm / 50 Ohm
-------------	------------------

Coaxial Cable
K_01252_D
苏州启道 — 中国区优势专业供应商
sales@qiidao.com
Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p / f^{0.5})$]

Coefficients:

a = 1.3

b = 0.3327

f_{max} = 6

P at 1GHz = 111

Frequency (GHz)	Nom. attenuation (dB / m)	Nom. attenuation (dB / ft)	Max. CW power (watt)
	sea level 25° C ambient temperature	sea level 25° C ambient temperature	sea level 40° C ambient temperature
0,3	0,81	0,247	203
0,6	1,21	0,368	143
0,9	1,53	0,467	117
1,2	1,82	0,556	101
1,5	2,09	0,637	91
1,8	2,34	0,714	83
2,1	2,58	0,787	77
2,4	2,81	0,857	72
2,7	3,03	0,925	68
3,0	3,25	0,990	64
3,3	3,46	1,054	61
3,6	3,66	1,117	59
3,9	3,86	1,178	56
4,2	4,06	1,238	54
4,5	4,25	1,297	52
4,8	4,45	1,355	51
5,1	4,63	1,412	49
5,4	4,82	1,468	48
5,7	5,0	1,524	46
6,0	5,18	1,579	45