

Coaxial Cable
K_02252_D

苏州启道 — 中国区优势专业供应商
sales@qiidao.com

Description

PTFE - 50 Ohm - double screen



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Steel, Copper+Silver plated	Strand-07	0.54 mm
Dielectric	PTFE (Polytetrafluoroethylene)		1.55 mm
Outer conductor	Copper, Silver plated	Braid, 96%	2 mm
Outer conductor	Copper, Silver plated	Braid, 91 %	2.5 mm
Jacket	FEP (Fluorinated ethylene propylene)	RAL 8015 - br	3 mm +/- 0.1

Print: HUBER+SUHNER K 02252 D 50 Ohm (PA no.)

Electrical Data

Impedance	50 Ω +/- 2
Operating Frequency	6 GHz
Capacitance	97 pF/m
Velocity of signal propagation	69 %
Signal delay	4.86 ns/m
Insulation resistance	≥ 1 x 10 ⁸ MQm
Min. screening effectiveness	≥ 80 dB (up to 6 GHz)
Max. operating voltage	≤ 0.85 kV _{rms} (at sea level)
Test voltage	1.7 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight		2.4 kg/100 m
Min. bending radius	static	18 mm
	repeated (for ≤ 50 bendings)	30 mm
	dynamic	45 mm

Environmental Data

Temperature range	-65 °C... +165 °C
Installation temperature	-20 °C... +60 °C
Flammability	IEC 60332-3, compliant
2011/65/EU (RoHS)	

Additional Information

Ordering Information

Order as	K_02252_D
----------	-----------

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group	U4 2 mm / 50 Ohm
-------------	------------------

Coaxial Cable
K_02252_D

苏州启道 — 中国区优势专业供应商

sales@qiidao.com
Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p / f^{0.5})$]

Coefficients:

a = 0.7648

b = 0.1301

f_{max} = 6

P at 1GHz = 149

Frequency (GHz)	Nom. attenuation (dB / m)	Nom. attenuation (dB / ft)	Max. CW power (watt)
	sea level 25° C ambient temperature	sea level 25° C ambient temperature	sea level 40° C ambient temperature
0,3	0,46	0,140	272
0,6	0,67	0,204	192
0,9	0,84	0,257	157
1,2	0,99	0,303	136
1,5	1,13	0,345	122
1,8	1,26	0,384	111
2,1	1,38	0,421	103
2,4	1,5	0,456	96
2,7	1,61	0,490	91
3,0	1,71	0,523	86
3,3	1,82	0,554	82
3,6	1,92	0,585	79
3,9	2,02	0,615	75
4,2	2,11	0,644	73
4,5	2,21	0,673	70
4,8	2,3	0,701	68
5,1	2,39	0,729	66
5,4	2,48	0,756	64
5,7	2,57	0,783	62
6,0	2,65	0,809	61