

## LNA Series

## 10KHz – 2000MHz Low Noise Amplifier

### Features

- Frequency: 10KHz - 2000MHz
- Gain: 26dB
- P<sub>1dB</sub>: +10dBm
- IP3: +23dBm
- Noise Figure: 3.2dB
- Internally Voltage Regulated
- Reverse Voltage Protected
- DC Power: 12V/45mA
- SMA Connector

### Picture



### Description

LNA-2000 is a wideband Low Noise Amplifier operates with frequency range from 10KHz to 2000MHz.


### Electrical Specifications @ +25 °C, Z<sub>in</sub> = Z<sub>out</sub> = 50 Ω, DC Voltage = +12V

Parameter	Unit	Minimum	Typical	Maximum
Frequency Range	MHz	0.01		2000
Gain S <sub>21</sub>	f = 10KHz	dB	22	24
	f = 20MHz	dB	24	26
	f = 1000MHz	dB	26	28
	f = 2000MHz	dB	23	25
Gain Flatness	dB		± 2.0	± 2.5
P <sub>1dB</sub>	f = 1000MHz	dBm	+10	+13
IP3	f = 1000MHz	dBm	+21	+23
Noise Figure	f = 1000MHz	dB	3.2	3.9
Reserve Isolation S <sub>12</sub>	f = 1000MHz	dB	-30	-35
Input VSWR S <sub>11</sub>	f = 1000MHz		1.5:1	2.0:1
Output VSWR S <sub>22</sub>	f = 1000MHz		1.4:1	2.0:1
DC Power Supply	V	11	12	18
Supply Current	mA		45	55


## LNA Series

## 10KHz – 2000MHz Low Noise Amplifier

### Gain S21, Isolation S12, Return Loss S11, S22 vs Frequency




### Noise Figure vs Frequency




## LNA Series

## 10KHz – 2000MHz Low Noise Amplifier

### Output P1dB vs Frequency



### Output IP3 vs Frequency



## LNA Series

## 10KHz – 2000MHz Low Noise Amplifier


### Absolute Maximum Ratings

Parameter	Absolute Maximum
Supply Voltage	+25V
RF Input Power	+13dBm
Operating Temperature	-40 °C to +85 °C
Storage Temperature	-55 °C to +125 °C

### ESD Sensitive Material



### Outline



	A	B	C	D	E	F	G	H	I	J
Inch	1.250	1.250	0.563	0.450	1.000	0.625	1.000	0.250	0.500	0.187
mm	31.75	31.75	14.29	11.43	25.40	15.88	25.40	6.35	12.70	4.76