

Coaxial Cable
RG_179_B/U

苏州启道 — 中国区优势专业供应商
sales@qiidao.com

Description

PTFE - 75 Ohm - single screen



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Steel, Copper+Silver plated	Strand-07	0.31 mm
Dielectric	PTFE (Polytetrafluoroethylene)		1.55 mm
Outer conductor	Copper, Silver plated	Braid, 94%	2 mm
Jacket	FEP (Fluorinated ethylene propylene)	RAL 8015 - br	2.54 mm +/- 0.13

Print: HUBER+SUHNER RG 179 B/U 75 Ohm (PA no.)

Electrical Data

Impedance	75 Ω +/- 3
Operating Frequency	3 GHz
Capacitance	63 pF/m
Velocity of signal propagation	69 %
Signal delay	4.83 ns/m
Insulation resistance	≥ 1 x 10 ⁸ MΩm
Min. screening effectiveness	≥ 41 dB (up to 1 GHz)
Max. operating voltage	≤ 0.75 kV _{rms} (at sea level)
Test voltage	1.5 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight	1.48 kg/100 m
Min. bending radius	static repeated (for ≤ 50 bendings) dynamic
	15 mm 25 mm 38 mm

Environmental Data

Temperature range	-65 °C... +165 °C
Installation temperature	-20 °C... +60 °C
Flammability	IEC 60332-1, compliant
2011/65/EU (RoHS)	

Additional Information

Ordering Information

Order as	RG_179_B/U
----------	------------

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group	U5 2 mm / 75 Ohm
-------------	------------------

Coaxial Cable
RG_179_B/U

苏州启道 — 中国区优势专业供应商

sales@qiidao.com
Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p / f^{0.5})$]

Coefficients:

a = 0.73

b = 0.1014

f_{max} = 3

P at 1GHz = 115

Frequency (GHz)	Nom. attenuation (dB / m)	Nom. attenuation (dB / ft)	Max. CW power (watt)
	sea level 25° C ambient temperature	sea level 25° C ambient temperature	sea level 40° C ambient temperature
0,15	0,3	0,091	297
0,3	0,43	0,131	210
0,45	0,54	0,163	171
0,6	0,63	0,191	148
0,75	0,71	0,216	133
0,9	0,78	0,239	121
1,05	0,85	0,260	112
1,2	0,92	0,281	105
1,35	0,99	0,300	99
1,5	1,05	0,319	94
1,65	1,11	0,337	90
1,8	1,16	0,354	86
1,95	1,22	0,371	82
2,1	1,27	0,387	79
2,25	1,32	0,403	77
2,4	1,37	0,419	74
2,55	1,42	0,434	72
2,7	1,47	0,449	70
2,85	1,52	0,464	68
3,0	1,57	0,478	66