

Coaxial Cable
RG_217_/U

苏州启道 — 中国区优势专业供应商
sales@qiidao.com

Description

PE-50 Ohm - double screen



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Copper	Wire	2.69 mm
Dielectric	PE (Polyethylene)		9.33 mm
Outer conductor	Copper	Braid, 96%	10.3 mm
Outer conductor	Copper	Braid, 94 %	11.2 mm
Jacket	PVC II (low migration)	RAL 9005 - bk	13.85 mm +/- 0.25

Print: HUBER+SUHNER RG 217/U 50 Ohm (PA no.)

Electrical Data

Impedance	50 Ω +/- 2
Operating Frequency	3 GHz
Capacitance	101 pF/m
Inductance	0.248 µH/m
Velocity of signal propagation	66 %
Signal delay	5.03 ns/m
Insulation resistance	≥ 1 x 10 ⁸ MΩm
Min. screening effectiveness	≥ 80 dB (up to 1 GHz)
Max. operating voltage	≤ 6 kV _{rms} (at sea level)
Test voltage	12 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight	30.1 kg/100 m
Min. bending radius	static repeated (for ≤ 50 bendings) 70 mm 140 mm

Environmental Data

Temperature range	-25 °C... +85 °C
Installation temperature	-20 °C... +60 °C
2011/65/EU (RoHS)	compliant

Additional Information

Ordering Information

Order as	RG_217_/U
----------	-----------

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group	U38 9 mm / 50 Ohm
-------------	-------------------

Coaxial Cable
RG_217_/U

苏州启道 — 中国区优势专业供应商

sales@qiidao.com
Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p / f^{0.5})$]

Coefficients:

a = 0.1469

b = 0.0549

f_{max} = 3

P at 1GHz = 600

Frequency (GHz)	Nom. attenuation (dB / m)	Nom. attenuation (dB / ft)	Max. CW power (watt)
	sea level 25° C ambient temperature	sea level 25° C ambient temperature	sea level 40° C ambient temperature
0,15	0,07	0,020	1549
0,3	0,1	0,030	1095
0,45	0,12	0,038	894
0,6	0,15	0,045	775
0,75	0,17	0,051	693
0,9	0,19	0,058	632
1,05	0,21	0,063	586
1,2	0,23	0,069	548
1,35	0,24	0,075	516
1,5	0,26	0,080	490
1,65	0,28	0,085	467
1,8	0,3	0,090	447
1,95	0,31	0,095	430
2,1	0,33	0,100	414
2,25	0,34	0,105	400
2,4	0,36	0,110	387
2,55	0,37	0,114	376
2,7	0,39	0,119	365
2,85	0,4	0,123	355
3,0	0,42	0,128	346