

Coaxial Cable
RG_223_/U-02

苏州启道 — 中国区优势专业供应商
sales@qiidao.com

Description

PE-50 Ohm - double screen



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Copper, Silver plated	Strand-19	0.9 mm
Dielectric	PE (Polyethylene)		2.93 mm
Outer conductor	Copper, Silver plated	Braid, 96%	3.6 mm
Outer conductor	Copper, Silver plated	Braid, 94 %	4.2 mm
Jacket	PVC II (low migration)	RAL 9005 - bk	5.3 mm +/- 0.15

Print: HUBER+SUHNER RG 223 U-02 50 Ohm (PA no.)

Electrical Data

Impedance	50 Ω +/- 2
Operating Frequency	6 GHz
Capacitance	101 pF/m
Velocity of signal propagation	66 %
Signal delay	5.03 ns/m
Insulation resistance	≥ 1 x 10 ⁸ MΩm
Min. screening effectiveness	≥ 83 dB (up to 1 GHz)
Max. operating voltage	≤ 2.5 kV _{rms} (at sea level)
Test voltage	5 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight	5.3 kg/100 m
Min. bending radius	static dynamic 26 mm 53 mm

Environmental Data

Temperature range	-25 °C... +85 °C
Installation temperature	-20 °C... +60 °C
2011/65/EU (RoHS)	compliant

Additional Information

Ordering Information

Order as	RG_223_/U-02
----------	--------------

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group	U9 3 mm / 50 Ohm
-------------	------------------

Coaxial Cable
RG_223_/U-02

苏州启道 — 中国区优势专业供应商
sales@qiidao.com

Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p / f^{0.5})$]

Coefficients:

a = 0.501

b = 0.067

f_{max} = 6

P at 1GHz = 120

Frequency (GHz)	Nom. attenuation (dB / m)	Nom. attenuation (dB / ft)	Max. CW power (watt)
	sea level 25° C ambient temperature	sea level 25° C ambient temperature	sea level 40° C ambient temperature
0,3	0,29	0,090	219
0,6	0,43	0,131	155
0,9	0,54	0,163	126
1,2	0,63	0,192	110
1,5	0,71	0,218	98
1,8	0,79	0,242	89
2,1	0,87	0,264	83
2,4	0,94	0,286	77
2,7	1,0	0,306	73
3,0	1,07	0,326	69
3,3	1,13	0,345	66
3,6	1,19	0,363	63
3,9	1,25	0,381	61
4,2	1,31	0,399	59
4,5	1,36	0,416	57
4,8	1,42	0,433	55
5,1	1,47	0,449	53
5,4	1,53	0,465	52
5,7	1,58	0,481	50
6,0	1,63	0,497	49