

Coaxial Cable
RG_393_/U

苏州启道 — 中国区优势专业供应商
sales@qiidao.com

Description

PFA - 50 Ohm - double screen



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Copper, Silver plated	Strand-07	2.46 mm
Dielectric	PFA (Perfluoroalkoxy)		7.25 mm
Outer conductor	Copper, Silver plated	Braid, 92%	8 mm
Outer conductor	Copper, Silver plated	Braid, 94 %	8.75 mm
Jacket	FEP (Fluorinated ethylene propylene)	RAL 8015 - br	9.9 mm +/- 0.25

Print: HUBER+SUHNER RG 393 U 50 Ohm (PA no.)

Electrical Data

Impedance	50 Ω +/- 2
Operating Frequency	6 GHz
Capacitance	95.9 pF/m
Velocity of signal propagation	70 %
Signal delay	4.79 ns/m
Insulation resistance	≥ 1 x 10 ⁸ MQm
Min. screening effectiveness	≥ 81 dB (up to 6 GHz)
Max. operating voltage	≤ 5.5 kV _{rms} (at sea level)
Test voltage	12.5 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight	22.9 kg/100 m
Min. bending radius	static repeated (for ≤ 50 bendings) dynamic
	60 mm
	100 mm
	150 mm

Environmental Data

Temperature range	-65 °C... +165 °C
Installation temperature	-20 °C... +60 °C
Flammability	IEC 60332-3-25,
2011/65/EU (RoHS)	compliant

Additional Information

Ordering Information

Order as	RG_393_/U
----------	-----------

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group	U33 7 mm / 50 Ohm
-------------	-------------------

Coaxial Cable
RG_393_/U
苏州启道 — 中国区优势专业供应商
sales@qiidao.com
Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p / f^{0.5})$]

Coefficients:

a = 0.1749

b = 0.129

f_{max} = 6

P at 1GHz = 1461

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (watt) sea level 40° C ambient temperature
0,3	0,13	0,041	2667
0,6	0,21	0,065	1886
0,9	0,28	0,086	1540
1,2	0,35	0,106	1334
1,5	0,41	0,124	1193
1,8	0,47	0,142	1089
2,1	0,52	0,160	1008
2,4	0,58	0,177	943
2,7	0,64	0,194	889
3,0	0,69	0,210	844
3,3	0,74	0,227	804
3,6	0,8	0,243	770
3,9	0,85	0,259	740
4,2	0,9	0,274	713
4,5	0,95	0,290	689
4,8	1,0	0,306	667
5,1	1,05	0,321	647
5,4	1,1	0,336	629
5,7	1,15	0,351	612
6,0	1,2	0,366	596