

Coaxial Cable
S_04262_D-09

苏州启道 — 中国区优势专业供应商
sales@qiidao.com

Description

PE Foam - 50 Ohm



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Copper, Silver plated	Wire	1.4 mm
Dielectric	SPE (Foamed Polyethylene)		3.78 mm
Outer conductor	Copper, Silver plated	Braid, 96%	4.2 mm
Outer conductor	Copper, Silver plated	Braid, 93 %	4.7 mm
Jacket	LSFH (modified polyethylene)	RAL 9005 - bk	5.7 mm +/- 0.1

Print: HUBER+SUHNER S 04262 D-09 50 Ohm (PA no.)

Electrical Data

Impedance	50 Ω +/- 2
Operating Frequency	6 GHz
Capacitance	82 pF/m
Velocity of signal propagation	82 %
Signal delay	4.08 ns/m
Insulation resistance	≥ 1 x 10 ⁸ MQm
Min. screening effectiveness	≥ 80 dB (up to 6 GHz)
Max. operating voltage	≤ 0.5 kV _{rms} (at sea level)
Test voltage	1 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight	6.3 kg/100 m
Min. bending radius	static repeated (for ≤ 50 bendings) 28 mm 58 mm

Environmental Data

Temperature range	-40 °C... +85 °C
Installation temperature	-20 °C... +60 °C
Flammability	IEC 60332-1, UL 1581 § 1080 (VW-1), FAR 25.869
Smoke density	EN 61034-2
Halogen test	IEC 60754
Uv resistance test	ISO 4892-2A
2011/65/EU (RoHS)	compliant

Additional Information

Ordering Information

Order as	S_04262_D-09
----------	--------------

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group	S16 4 mm / 50 Ohm
-------------	-------------------

Coaxial Cable
S_04262_D-09

苏州启道 — 中国区优势专业供应商

sales@qiidao.com
Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p / f^{0.5})$]

Coefficients:

a = 0.2938

b = 0.0401

f_{max} = 6

P at 1GHz = 127

Frequency (GHz)	Nom. attenuation (dB / m)	Nom. attenuation (dB / ft)	Max. CW power (watt)
	sea level 25° C ambient temperature	sea level 25° C ambient temperature	sea level 40° C ambient temperature
0,3	0,17	0,053	232
0,6	0,25	0,077	164
0,9	0,31	0,096	134
1,2	0,37	0,113	116
1,5	0,42	0,128	104
1,8	0,47	0,142	95
2,1	0,51	0,155	88
2,4	0,55	0,168	82
2,7	0,59	0,180	77
3,0	0,63	0,192	73
3,3	0,67	0,203	70
3,6	0,7	0,214	67
3,9	0,74	0,225	64
4,2	0,77	0,235	62
4,5	0,8	0,245	60
4,8	0,84	0,255	58
5,1	0,87	0,265	56
5,4	0,9	0,274	55
5,7	0,93	0,283	53
6,0	0,96	0,293	52